



THE INDUSTRY STANDARD FOR STEEL IBCs



SOLUTIONS IN BULK HANDLING

www.snydernet.com

SUPER TAINER

SUPERTAINER

Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling

Robotic manufacturing process ensures consistent high weld quality and assurance of container integrity.

22 5/16" cover with EPDM Gasket and 2" Rieke Fusible Vent/or 3" fusible vent, so cover can remain sealed during filling. 2" bung fitting optional.



Lifting lugs enable container to be lifted overhead via hoist or crane apparatus.



Available in 304, 316 stainless or painted carbon steel for optimum durability and corrosion resistance.

Temperature control devices can be integrated within an IBC for heating and cooling requirements.

Unique stamped bottom provides "no heel" bottom for total drainage.

DOT UN31A permits shipment of flammable and combustible liquids as authorized by Title 49 CFR.

3 way fork entry for both pallet jack and forklift access.

Multiple valve arrangements are available to meet different function and connection requirements.



2" Ball Valve Outlet Assembly

Specifications

Supertainer 42"x48" Base		
Capacity	Height	Weight
180 Gallon	29 1/4"	344 lbs.
250 Gallon	35 1/4"	384 lbs.
300 Gallon	41 1/4"	425 lbs.
350 Gallon	47 1/4"	465 lbs.
446 Gallon	59 1/4"	546 lbs.
550 Gallon	71 1/4"	627 lbs.
Supertainer 54"x54" Base		
793 Gallon	73 3/4"	1085 lbs.

Supertainer 42"x42" Base		
Capacity	Height	Weight
160 Gallon	30 1/4"	318 lbs.
250 Gallon	42 1/4"	346 lbs.
300 Gallon	48 1/4"	437 lbs.
390 Gallon	60 1/4"	512 lbs.
478 gallon	72 1/4"	591 lbs.

Additional Options:

Sanitary Designs.
Center Drain w/fork channels.
Custom Designs.

Supertainer LX 42"x48" Base		
Capacity	Height	Weight
350 Gallon	47"	416 lbs.

A lighter weight construction, more economical version...same high weld quality and assurance of integrity.

Note: Height is from the floor to the top of the tank. Overall height will be 3 3/4" taller to top of lifting lugs.

Approximate weights provided are for Stainless Steel. Other sizes available upon request.

Phone: 1-888-IBC-TOTE (888-422-8683) • sales@snydernet.com • www.snydernet.com

OPTIONS & ACCESSORIES

Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling

A Wide variety of options and accessories enables you to customize your Supertainer to your application and your budget.



Standard 2" Ball Valve.
Other optional sizes available.



Valve Options
Sanitary, Ball, Butterfly.



Quick Connect Adapters.



Pressure/Vacuum Vents.



Drum Lid Clamp Rings
Bolted & Lever-Lock Styles.



3" Fusible Vent.



2" Rieke Fusible Vent.



Crossbar & Standard Bung Fittings.



Lid Gaskets.



Drum Lids in 304 & 316 Stainless Steel & Carbon Steel.




2" 15° Offset Male Quick Connect Adapter.



3" GITS 5 in 1 Fusible P/V Vent.



Insulation Blanket with optional heating elements for all Supertainers sizes.



Replacement Decals.



IBC Stands.



All Snyder IBCs are available with stacked discharge feed systems that allow the top tank to drain into the bottom tank.



Cooling/Heating Jacket panels.



Heating Coils: Base coil, Cork screw coil w/protective collar.



At-A-Glance Gauge:
Designed for long-life and easy readability...
"At-A-Glance" liquid level indicator.



Supertainer is available in carbon steel.

Phone: 1-888-IBC-TOTE (888-422-8683) • sales@snydernet.com • www.snydernet.com

Solutions in Bulk Handling

Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling • Solutions in Bulk Handling



Plastic IBCs

Snyder's unique all polyethylene IBC designs are lightweight, durable and corrosion resistant. Available in a wide variety of shapes and sizes up to 550 gallons, these IBCs are ideal for both hazardous and non-hazardous liquid applications. Rotationally molded in wall thicknesses up to a half inch, Snyder's plastic IBCs provide some of the industry's highest useful-life-to-cost ratios.



Composite IBCs

Some applications require the combined use of both steel and plastic in an IBC design to meet specific requirements. Snyder offers the industry's broadest range of composite IBCs in sizes up to 550 gallons, where a polyethylene bottle is encased in a heavy-duty steel cage. Certain plant specifications or warehouse space considerations may require the use of a composite IBC, and Snyder has the perfect solution in these cases.



Viscous Liquid IBCs

Some liquids don't flow freely through a standard IBC bottom discharge design, and require help to drain material efficiently and completely. Snyder has a wide array of IBC design types to promote better drain flow of materials with varying levels of viscosity. Be it a cone bottom or follower plate design, Snyder's viscous liquid IBCs can solve your company's challenges in handling liquid materials with higher viscosities.



Custom Container Designs

In addition to Snyder's extensive standard product offering, some of our greatest success stories stem from custom container designs to meet specific customer requirements. Snyder's engineering team is a recognized leader in design innovation, and is driven to work with customers to develop the best performing container at the lowest possible cost.



Phone: 1-888-IBC-TOTE (888-422-8683) • sales@snydernet.com • www.snydernet.com
Snyder Industries, Inc. - Corporate Offices • P.O. Box 4583 • Lincoln, NE • 68504
Other manufacturing Locations: Chowchilla, CA • Mancelona, MI • Marked Tree, AR • Philippi, WV