



Jumbo Drum - Stainless Steel

Sii P/N	Capacity	OAH
18971	250 Gal	46.8
18972	330 Gal	58.8
18973	380 Gal	66.8
18974	440 Gal	74.8
18975	500 Gal	82.8

This tank has been tested and certified to meet D.O.T. requirements per 49 C.F.R., Part 178, Subpart N and Subpart O for metal intermediate bulk containers for liquids intended for the transportation of hazardous materials. (Identification code 31A1 Y)

Meets Packing Group II and Group III tests for liquids up to 1.9 specific gravity.

See 49 C.F.R. Part 172.101 Hazardous Materials Table for packaging authorizations.

Notes:

1. Tank is designed and constructed in accordance with U.N. Specifications
2. Tank is air tested @ 3 PSI
3. All welds cleaned of slag and spatter
4. Tank interior and exterior are electro-cleaned
5. Drum lid to be installed by: Strike ring around circumference with a mallet then tighten bolt with a wrench. Repeat until bolt tightening resistance does not change (Ref: 40 lb-ft)
6. 2IN bung to be installed 1/8-1/6 rotation beyond solid gasket contact (Ref: 30 lb-ft)

© Copyright Snyder Industries, Inc. 2007



(All dimensions in inches.)

JUMBO DRUM 45.5 OD STAINLESS STEEL

Standard Jumbo Drum IBC
 45.5 OD

SNYDER INDUSTRIES, INC.