

# PLASTIC COATINGS CORPORATION

## MATERIAL SAFETY DATA SHEET

Revision Date: January 2, 2008

### SECTION I - PRODUCT IDENTIFICATION

**Product Name:** JAXSAN 602  
**Manufacturer:** Plastic Coatings Corporation  
**Manufacturing Address:** 4904 Teays Valley Rd., Scott Depot, WV 25560  
**Mailing Address:** P.O. Box 1068, St. Albans, WV 25177  
**Telephone:** (304) 755-9151    **FAX:** (304) 755-0229    **Emergency Telephone:** (304) 344-9218  
**Product Class:** Acrylic latex elastomeric paint/ insulation sealant

### HAZARDOUS MATERIAL IDENTIFICATION SYSTEM RATING

**Health: 1**      **Flammability: 0**      **Reactivity: 0**      **Personal Protection: B**

### SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS. NUMBER	WT. %	OCCUPATIONAL EXPOSURE LIMITS	
			TLV	PEL
Jaxsan 602 does not contain reportable or significant amounts of hazardous materials as defined in 40 CFR part 300 or 219 CFR 1293.1200				
PRINCIPAL INGREDIENTS:				
Acrylic latex				None Established
Water	7732-18-5			None Established
Alumina trihydrate	21645-51-2			None Established
Magnesium silicate	14907-96-6			None Established
Titanium dioxide	13463-67-7			None Established
Volatile Organic Contents (VOC) as packaged minus water: 0.04 lb./gal. (5 gm./l.)				

### SECTION III - PHYSICAL DATA

<b>Boiling point:</b>	<b>212 degrees F.</b>	<b>Weight per gallon:</b>	<b>11.5 pounds</b>
<b>Evaporation rate:</b>	<b>Same as water</b>	<b>Percent volatile by volume:</b>	<b>45</b>
<b>Vapor density:</b>	<b>Lighter than air</b>	<b>ppm:</b>	<b>9-9.5</b>
<b>Typical appearance:</b>	<b>Heavy bodied fibrous paint/mastic paste.</b>		