



THE INDUSTRY STANDARD FOR STEEL IBCS



SOLUTIONS IN BULK HANDLING

www.snydernet.com

**S
U
P
E
R
T
A
I
N
E
R**

SUPERTAINER

IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING

Robotic manufacturing process ensures consistent high weld quality and assurance of container integrity.

22 5/16" cover with EPDM Gasket and 2" Rieke Fusible Vent/or 3" fusible vent, so cover can remain sealed during filling. 2" bung fitting optional.



Lifting Lugs enable container to be lifted overhead via hoist or crane apparatus.



Available in 304, 316 stainless or painted carbon steel for optimum durability and corrosion resistance.

Unique Stamped Bottom provides "no heel" bottom for total drainage.

3 Way Fork Entry for both pallet jack and forklift access.



Temperature control devices can be integrated within an IBC for heating and cooling requirements.

DOT UN31A permits shipment of flammable and combustible liquids as authorized by Title 49 CFR.

Multiple valve arrangements are available to meet different function and connection requirements.



2" Ball Valve Outlet Assembly

SPECIFICATIONS

| Supertainer 42" x 48" Base | | |
|----------------------------|---------|-----------|
| Capacity | Height | Weight |
| 180 Gallon | 29 1/4" | 344 lbs. |
| 250 Gallon | 35 1/4" | 384 lbs. |
| 300 Gallon | 41 1/4" | 425 lbs. |
| 350 Gallon | 47 1/4" | 465 lbs. |
| 446 Gallon | 59 1/4" | 546 lbs. |
| 550 Gallon | 71 1/4" | 627 lbs. |
| Supertainer 54" x 54" Base | | |
| 793 Gallon | 73 3/4" | 1085 lbs. |

| Supertainer 42" x 42" Base | | |
|----------------------------|---------|----------|
| Capacity | Height | Weight |
| 160 Gallon | 30 1/4" | 318 lbs. |
| 250 Gallon | 42 1/4" | 346 lbs. |
| 300 Gallon | 48 1/4" | 437 lbs. |
| 390 Gallon | 60 1/4" | 512 lbs. |
| 478 Gallon | 72 1/4" | 591 lbs. |

| Supertainer 42" x 48" Base | | |
|----------------------------|--------|----------|
| Capacity | Height | Weight |
| 350 Gallon | 47" | 416 lbs. |

A lighter weight construction, more economical version...same high weld quality and assurance of integrity.

Additional Options: Sanitary Designs; Center Drain with fork channels; Custom Designs.

Note: Height is from the floor to the top of the tank. Overall height will be 3 3/4" taller to the top of lifting lugs.

Approximate weights provided are for Stainless Steel. Other sizes available upon request.

Phone: 1-888-IBC-TOTE (888-422-8683) • sales@snydernet.com • www.snydernet.com

OPTIONS & ACCESSORIES

G • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN

A wide variety of options and accessories enables you to customize your Supertainer to your application and your budget.



Standard 2" Ball Valve. Other optional sizes available.



Valve Options
Sanitary, Ball Butterfly



Quick Connect Adapters



Pressure/Vacuum Vents



Drum Lid Clamp Rings
Bolted & Lever-Lock Styles



2" Fusible Vent



2" Rieke Fusible Vent



Crossbar & Standard Bung Fittings



Lid Gaskets



Drum Lids in 304 & 316 Stainless Steel & Carbon Steel



2" 15° Offset Male Quick Connect Adapter



3" GITS 5 in 1 Fusible P/V Vent




Insulation Blanket with optional heating elements for all Supertainer sizes.



Replacement Decals



IBC Stands



Cooling/Heating Jacket Panels



Heating Coils: Base Coil; Cork Screw Coil w/protective collar



At-A-Glance Gauge: designed for long-life and easy readability. "At-A-Glance" liquid level indicator.



All Snyder IBCs are available with stacked discharge feed systems that allow the top tank to drain into the bottom tank.



Supertainer is available in carbon steel.

SOLUTIONS IN BULK HANDLING

SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING



Plastic IBCs

Snyder's unique all polyethylene IBC designs are lightweight, durable and corrosion resistance. Available in a wide variety of shapes and sizes up to 550 gallons, these IBCs are ideal for both hazardous and non-hazardous liquid applications. Rotationally molded-in wall thicknesses up to one half inch, Snyder's plastic IBCs provide some of the industry's highest useful-life-to-cost ratios.



Composite IBCs

Some applications require the combined use of both steel and plastic in an IBC design to meet specific requirements. Snyder offers the industry's broadest range of composite IBCs in sizes up to 550 gallons, where a polyethylene bottle is enclosed in a heavy duty steel cage. Certain plant specifications or warehouse space considerations may require the use of a composite IBC, and Snyder has the perfect solution in these cases.



Viscous Liquid IBCs

Some liquids don't flow freely through a standard IBC bottom discharge design, and require help to drain material efficiently and completely. Snyder has a wide array of IBC design types to promote better drain flow of materials with varying levels of viscosity. Be it a cone bottom or follower plate design, Snyder's viscous liquid IBCs can solve your company's challenges in handling liquid materials with higher viscosities.



Custom Container Designs

In addition to Snyder's extensive standard product offering, some of our greatest success stories stem from custom container designs to meet specific customer requirements. Snyder's engineering team is a recognized leader in design innovation, and is driven to work with customers to develop the best performing container at the lowest possible cost.



Phone: 1-888-IBC-TOTE (888-422-8683) • sales@snydernet.com • www.snydernet.com
Snyder Industries - Corporate Offices • 6940 "O" Street, Suite 100 • Lincoln, NE • 68510
Other manufacturing Locations: Chowchilla, CA • Mancelona, MI • Marked Tree, AR • Philippi, WV